

PERFORMANCE MEETS RELIABILITY

X-PROTINT Automatic Dispenser

X-PROTINT comes from the stable of X-Series dispensers and offers high-quality tinting solutions with precision and speed. It was the perfect machine in response to the widespread demand from customers for a simple modular automatic paint dispenser



Fast and precise

X-PROTINT guarantees tinting with a dramatic speed and reliability



Ease of operations

No more clorant-related mistints with AutoDrive™ technology



Sturdy design

Robust steel-armored design offering business owners at high turnover locations with greater capacity and speed



Software compatible

Powered by PrismaPro2 software and compatible with mobile dispensing app PrismaRT



Future-ready technology

Future ready with VOC-free colorants



Operator-friendly

Packed with innovative features for easy operations and self-maintenance

X-PROTINT in Spotlight

Specifications & Technical Data

General

- Automatic sequential
- Water based, universal
- Solvent based (optional)
- Bi-directional turn table

Canisters

- Up to 16 canisters
- Material: Polymeric (POM)
- Size: 12 x 2.3 Lt + 4 x 4.6 Lt
- Click-on-click-off
- Patented optimal stirrer design

Pump

- Piston pump
- Size- 43 ml
- Flow rate- 0.5 Lt/min
- Min. dispense- 0.077ml (1/384 fl. oz.)
- Nozzle diameter- 4 mm
- Polymeric needle valve
- Seals material- Viton, Viton Extreme
- Calibration- 1st machine only.
Subsequent machines copied
calibration files. Calibration lasts machine life time

Nozzles

- Air tight - Integrated nozzle closures
- Nozzle cleaning system- passive brush



Dimension & Weight

- HWD- 123 x 82 x 87 cm
- Filling height- 115 cm
- Packaging HWD- 142 x 98 x 98 cm
- Net weight- 128 kg



Can table

- Manual can shelf
- Dimensions: 38 x 35 cm (W x D)
- Can loading height: 25 cm
- Max. can height: 41 cm (50 cm when no shelf)
- Optical can sensor

Maintenance & Operations

- Low level (only purge & brush clean)
- Low TCO
- Ease of use
- Minimal operator training
- Visual LED error indicator
- Robust design - dust & rodent proof, flood resistant up to 40 cm

Software

- Easy to use desktop application PrismaPro2
- Local language compatible
- PrismaRT mobile app compatible



Power supply & safety

- 110V/230V +/- 10%, 50Hz/60Hz
- CE/UL, SASO Certificate

Experience faster and precise tinting with **X-PROTINT**



Stay connected with us



For more information,
visit our website

