TI ELEMENT 4

ACHIEVE MORE WITH AN ALL-ROUNDER

Ideal for: Medium-volume daily tinting operations

KEY BENEFITS



SIMPLE & ROBUST

Strong steel frame made to last. No assembly needed; easy to set up and use, with minimal training



SCALABLE & VERSATILE

A larger dispense bay and more canisters, with flexibility up to 24 or 32 canisters. Compatible with any colorant system



ENHANCED PERFORMANCE

Flow rate of up to 558 ml/min (19 oz) and minimum dispense of 0.050ml (1/512th of a shot), for enhanced speed and accuracy



RELIABLE & SUSTAINABLE

The ZeroPurgeTM piston pump ensures 100% recirculation, effectively eliminating idle colorants that can lead to dry nozzles and blockages. With our innovative AutoDriveTM technology, the pump seamlessly operates even with the most challenging colorants, ensuring reliable performance and preventing costly mistints.



ULTRA LOW MAINTENANCE

Daily maintenance in a matter of minutes with a simple cleaning of the brush, nozzle, and can shelf. The new wet brush system with a magnetic sensor extends cleaning intervals and ensures proper brush placement for smooth operation



SMART & CONNECTED

Seamless integration with Tintelligence apps suite for more intuitive dispensing, real-time updates, remote fleet management and quick service resolution



SOFTWARE

Flexible software options to best meet your business needs

- (1) **PrismaPro 2**: TI ELEMENT 4 is compatible with our existing dispensing software
- (2) **Tintelligence:** From a simple dispensing solution to a full suite of advanced digital applications, choose the package that best suits your needs.









- Basic: Simple, more intuitive desktop dispensing solution for faster order fulfillment
- Fleet Management: Real-time, remote fleet monitoring and analytics for faster, data-driven decisions
- Color Management: Fleet dispense database management and dispensing solution for always up-to-date formula books
- Full Suite: Comprehensive fleet and color management solution

SERVICE & SUPPORT

Our customer commitment continues long after the sale with:

- Extensive self-serviceability features with manuals for guidance
- · Quick installation and training
- Robust Service Network
- Factory technicians for technical support

TECHNICAL SPECIFICATIONS

CANISTER	Canisters	up to 32
	Canister configuration	Multiple configurations with 1.3 L, 2.3 L and 4.6 L
	Canister Type	Water, solvent and universal
	Canister Material	POM (Solvent)
TURNTABLE	Turntable type	Bi-directional
	Flow rate	up to 558 ml/min (19 oz)
	Refill position	Front
	Filling height	78 cm
PUMP	Pump type	ZeroPurge™ Piston Pump
	Min. Dispense	0.050 ml (1/512th of a shot)
	Valve type	Stainless steel ball valve
	Pump size	43 ml
	Pump seal material	Viton Extreme
	Calibration	One-time calibration. Lasts machine lifetime
MACHINE	Dimensions (HxWxD)	125 x 82 x 87 cm
	Weight	134 kg for 32 canister configuration
	Enclosure	Metal
CAN TABLE	Dispense tray	Manual
	Maximum can height	41 cm (50 cm no shelf)
	Optical can sensor	Yes
BRUSH	Brush type	sliding brush
	Brush container material	POM
	Motorized brush	standard
PACKAGING & TRANSPORT	Dimensions (HxWxD)	142 x 98 x 98 cm
	Assembly needed	No
	Units in 40ft container	24
	Units in 20ft container	12
	Weight	163 kg for 32 canister configuration
ACCESSORIES	Drip plate	Yes
	Heating set	Optional
	Ventilation interface	Optional
	Can positioning light	Optional
	Can table extender	Optional

ACHIEVE MORE WITH THE ROBUST,

RELIABLE AND VERSATILE TI ELEMENT 4

- Simple operation requires minimal training and support
- ✓ Strong and robust, built to last
- ✓ Self-serviceable machine, requiring very few service visits
- Easy and minimal maintenance
- Eliminate colorant wastage and mistints
- Easily manage peak hours and large can orders
- Keep spare inventory low with common parts

Elevate your daily tinting operations with **TI ELEMENT 4** and experience new levels of performance and efficiency.

Contact us to learn more!



