

Compact, simple, and reliable tinting
at the **LOWEST TCO**

Ideal for: Low-volume daily tinting operations

KEY BENEFITS



SMALL & SIMPLE

Easy to assemble and operate



ACCURATE & REPEATABLE TINTING

Precisely dispenses down to 0.050ml (1/512th of a shot), every time



SHORTER DISPENSE CYCLE TIME

Bi-directional turntable and faster dispense speed cut down cycle time, enabling quicker order fulfillment



LARGER DISPENSE BAY

Accommodates cans up to 47cm in height



ULTIMATE RELIABILITY

Proven piston pump and AutoDrive™ technology to eliminate mistints and keep the dispenser always ready for action



ULTRA LOW MAINTENANCE

The ZeroPurge™ piston pump, magnetic clamp brush, easier canister click 'n release system and manually movable turntable make maintenance minimal and easy



SMART & CONNECTED

Seamless integration with Tintelligence apps suite for more intuitive dispensing, real-time updates, remote fleet management and quick service resolution



SOFTWARE

Flexible software options to best meet your business needs

(1) **ColorPro/PrismaPro:** TI ELEMENT 2 is compatible with our existing dispensing software

(2) **Tintelligence:** From a simple dispensing solution to a full suite of advanced digital applications, choose the package that best suits your needs.



- **Basic:** Simple, more intuitive desktop dispensing solution for faster order fulfillment
- **Fleet Management:** Real-time, remote fleet monitoring and analytics for faster, data-driven decisions
- **Color Management:** Fleet dispense database management and dispensing solution for always up-to-date formula books
- **Full Suite:** Comprehensive fleet and color management solution

SERVICE & SUPPORT

Our customer commitment continues long after the sale with:

- Extensive self-serviceability features with manuals for guidance
- Quick installation and training
- Robust Service Network
- Factory technicians for technical support

MINIMIZE YOUR TCO LIKE NEVER BEFORE WITH TI ELEMENT 2

- ✓ Simple operations requires minimal training and support
- ✓ Self-serviceable machine, requiring very few service visits
- ✓ Easily transportable and fits in any small-medium store
- ✓ Eliminate colorant wastage and mistints
- ✓ Easily manage peak hours and large can orders
- ✓ Keep spare inventory low with common parts

Elevate your daily tinting operations with **TI ELEMENT 2** and experience new levels of performance and efficiency. Contact us to learn more!

TECHNICAL SPECIFICATIONS

CANISTER	Canisters	16
	Canister configuration	16 x 2,3L (16 canisters) 12 x 1,3L & 12 x 2,3L (24 canisters)
	Canister Type	Water, Universal, Solvent
TURNTABLE	Turntable type	Bi-directional
	Max Speed	330 ml/min (11 oz/min)
	Refill position	Front
	Filling height (cm)	120
PUMP	Pump type	ZeroPurge™ Piston Pump
	Min. Dispense	0.050 ml (1/512th of a shot)
	Valve type	Stainless steel ball valve
	Pump size	31 ml
	Pump seal material	Viton Extreme
	Calibration	One-time calibration. Lasts machine lifetime
MACHINE	Dimensions (HxWxD)	124 x 72 x 85 cm
	Weight	49 kg for 16 canister configuration
	Enclosure	Plastic
CAN TABLE	Dispense tray	Manual
	Maximum can height	47 cm
	Optical can sensor	Yes
BRUSH	Brush type	Magnetic click with sensor
	Brush container material	POM
PACKAGING & TRANSPORT	Dimensions (HxWxD)	110 x 76 x 96 cm
	Assembly needed	Yes
	Weight	67 kg for 16 canister configuration
ACCESSORIES	Drip plate	Optional
	Top cover	Standard
	Monitor keyboard arm	Optional

