

WHERE SIMPLICITY MEETS DURABILITY

KEY BENEFITS



SIMPLE AND ROBUST

Built from the best of the TI ELEMENT platform, the TI ELEMENT 2S pairs trusted dispensing technology with a durable steel frame designed for everyday tinting environments.



ACCURATE & REPEATABLE TINTING

Precisely dispenses down to 0.050 ml (1/512th of a shot) for reliable color accuracy and consistent tinting results every time.



SHORTER DISPENSE CYCLE TIME

A bi-directional turntable and optimized dispense speed help reduce cycle times and improve productivity during busy periods.



ULTIMATE RELIABILITY

The ZeroPurge™ piston pump with AutoDrive™ technology provides continuous colorant recirculation and dependable performance, even when dispensing challenging colorants.



ULTRA LOW MAINTENANCE

Self-serviceable features, easy canister removal and minimal maintenance requirements reduce downtime and lower service costs.



SMART & CONNECTED

Seamlessly connects with the Tintelligence application suite for intuitive dispensing, fleet visibility and faster service support.



SOFTWARE

Flexible software options to best meet your business needs

Tintelligence: From a simple dispensing solution to a full suite of advanced digital applications, choose the package that best suits your needs.



TI INSIGHT



TI SERVICE



TI DATA HUB



TI DISPENSE



TI ASSIST

- **Basic:** Simple, more intuitive desktop dispensing solution for faster order fulfillment
- **Fleet Management:** Real-time, remote fleet monitoring and analytics for faster, data-driven decisions
- **Color Management:** Fleet dispense database management and dispensing solution for always up-to-date formula books
- **Full Suite:** Comprehensive fleet and color management solution

SERVICE & SUPPORT

Our customer commitment continues long after the sale with:

- Extensive self-serviceability features with manuals for guidance
- Quick installation and training
- Robust Service Network
- Factory technicians for technical support

MINIMIZE YOUR TCO LIKE NEVER BEFORE WITH TI ELEMENT 2S

- ✓ Simple operations requires minimal training and support
- ✓ Self-serviceable machine, requiring very few service visits
- ✓ Easily transportable and fits in any small-medium store
- ✓ Eliminate colorant wastage and mistints
- ✓ Easily manage peak hours and large can orders
- ✓ Keep spare inventory low with common parts



TECHNICAL SPECIFICATIONS

CANISTER	Canisters	up to 24
	Canister configuration	16 x 2,3L (16 canisters) 12 x 1,3L & 12 x 2,3L (24 canisters)
	Canister Type	Water, Solvent and Universal
TURNTABLE	Turntable type	Bi-directional
	Max Speed	330 ml/min (11 oz/min)
	Refill position	Front
	Filling height (cm)	120
PUMP	Pump type	ZeroPurge™ Piston Pump
	Minimum dispense	0.050 ml (1/512th of a shot)
	Valve type	Stainless steel ball valve
	Pump size	31 ml
	Pump seal material	Viton Extreme
	Calibration	One time calibration. Lasts machine lifetime
MACHINE	Dimensions (HxWxD)	125 x 82 x 87 cm
	Weight	84 kg for 16 canister configuration
	Enclosure	Steel and plastic
CAN TABLE	Dispense tray	Manual
	Maximum can height	50 cm
	Optical can sensor	Yes
BRUSH	Brush type	Slide out brush
	Brush container material	POM
PACKAGING & TRANSPORT	Dimensions (HxWxD)	142 x 98 x 98 cm
	Assembly needed	Yes
	Weight	114 kg for 16 canister configuration
ACCESSORIES	Can Table Extender	Optional

Elevate your daily tinting operations with **TI ELEMENT 2S** and experience new levels of performance and efficiency.

Contact us to learn more!